


Datasheet	Foil bag preheater	Tmax 65°C
-----------	--------------------	-----------

Features and benefits
<ul style="list-style-type: none"> <li>• Suitable for up to 600 ml foil bags</li> <li>• Intrinsically safe PTC heating element (Tmax 65°C): Prevents uncontrolled heating in the event of a fault</li> <li>• Electronic temperature controller, easily adjustable via three buttons</li> <li>• Carrying strap for easy transport</li> <li>• Silicone-free</li> <li>• EPP housing: Energy-efficient and impact-resistant</li> </ul>

Technical data	HC065-F604-230V-R	
	Operating voltage	230 VAC
	Rated power	300 W (@10°C)
	Protection class	I (protective earth)
	IP protection class	IP30
	Housing	EPP
	Weight	4,3 kg
	Connection cable (enclosed) with type F plug	1,5 m
	Dimensions (LxWxH)	405 x 180 x 370 mm

Description
<p>The completely new film bag preheater was developed for heating up to 600 ml film bags and for use in harsh construction sites and industrial operations. This allows products such as adhesives and sealants to be heated to the optimum processing temperature.</p> <p>Lightweight and resistant to dirt, knocks and drops, it can be transported to the place of use using the carrying strap. Once warmed up, the foil bags retain their temperature for a long time even without a power supply.</p>